



NOTE :
 - MARKING "A" is used to identify "STANDARD" terminal
 - CRIMPING SPECIFICATION ACCORDING TO AS-64322-001

2	BOX TERMINAL	STAINLESS STEEL thickness=0.15 mm
1	BODY TERMINAL	high conductivity copper alloy thickness=0.2 mm
MARK	DESIGNATION	MATERIAL

PART NUMBER	CONTACT AREA	CRIMPING AREA	UNDERLAYER	CRIMPING RANGE (mm ²)	A±0.2	B±0.2	rC ^{+0.15} _{-0.1}	D±0.2	E±0.2	rF±0.1	WEIGHT (g)
0643221029	Sn	Sn	Ni	0.75	2.5	2.4	0.6	3.3	2.8	0.75	0.119
0643221219	Au 1.27μ MINI	Sn	Ni	0.50	2.3	2.2	0.6	3.1	2.6	0.75	0.117
0643221039	Sn	Sn	Ni	0.50	2.3	2.2	0.6	3.1	2.6	0.75	0.117
0643221239	Au 1.27μ MINI	Sn	Ni	0.22 to 0.44	2.0	1.7	0.6	3.1	2.6	0.75	0.112
0643221019	Sn	Sn	Ni	0.22 to 0.44	2.0	1.7	0.6	3.1	2.6	0.75	0.112
0643221229	Au 1.27μ MINI	Sn	Ni	0.22 to 0.44	2.0	1.7	0.6	3.1	2.6	0.75	0.112

(SKC) COTES CARACTERISTIQUES SPECIALES
 SPECIAL KEY CHARACTERISTICS
 ■ INDICATION DIMENSIONS S.P.C
 DENOTES S.P.C DIMENSIONS
 ● INDICATION DIMENSIONS CRITIQUES
 DENOTES CRITICAL DIMENSIONS
 ● INDICATION DIMENSIONS FONCTIONNELLES
 DENOTES FUNCTIONAL DIMENSIONS
 QUANTITE PAR FEUILLE INDIVIDUELLE
 QUANTITY PER INDIVIDUAL SHEET
 ■ 1 ● 0 ● 4 (SKC) 0

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS	SCALE	CURRENT REV	DESC:
mm	20:1		NX RE-MASTERING
GENERAL TOLERANCES (UNLESS SPECIFIED)			
ANGULAR TOL	± 2.0°	EC NO: 114689	
4 PLACES	± 0.1	DRWN:	SSUVARNA 2017/07/05
3 PLACES	± 0.1	CHK'D:	SLAFAURE 2018/06/04
2 PLACES	± 0.1	APPR:	SLAFAURE 2018/06/14
1 PLACE	± 0.1	INITIAL REVISION:	
0 PLACES	± 0.1	DRWN:	FPAROLARI 2007/09/17
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPR:	LSTICKEIR 2007/09/17
FIRST ANGLE PROJECTION	DRAWING	SERIES	
	A1-SIZE	64322	

molex			
CP RCPT TRM 0.6			
PRODUCT CUSTOMER DRAWING			
DOCUMENT NUMBER	DOC TYPE	DOC PART	REVISION
SD-64322-001	PSD	000	E1
MATERIAL NUMBER	CUSTOMER	SHEET NUMBER	
SEE CHART	GENERAL MARKET	1 OF 1	