



- 1 DIMENSIONS IN BRACKETS ARE IN INCHES.
- 2 CONTINUOUS STRIP ON REELS.
- 3 FOR FOREIGN PRODUCTION ONLY.
- 4 NO RIB IN LOCKING LANCE.
- 5 NO STRESS RELIEVING
- 6 REELED WITH INTERLEAVING PAPER
- 8 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

△/4	---	TIN	BRASS	2.54 - 4.32	0.8 - 2.0 mm ²	±0.025	42100-9
△/3	---	TIN	BRASS				
△/3	---	---	BRASS	[.100 - .170]	[18 - 14]	0.81 [.032 ±.001]	2-42100-1
△/8	OBSOLETE	TIN	BRASS				1-42100-2
△/8	OBSOLETE	1-42238-1	BRASS	[.100 - .170]	[18 - 14]	0.81 [.032 ±.001]	1-42100-4
△/4	---	SILVER	BRASS				42100-3
△/4	---	TIN	BRASS	[.100 - .170]	[18 - 14]	0.81 [.032 ±.001]	42100-2
△/4	---	---	BRASS				42100-1
	LOOSE PIECE	FINISH	MATERIAL	INSULATION RANGE	WIRE SIZE	TAB THK	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	JR RUTH	2/5/88	STE TE Connectivity
DIMENSIONS: mm[INCHES]		CHK	MS FEHER	2/5/88	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	C MEYERS	2/8/88	
0 PLC ± -		NAME		RECEPTACLE, FASTON-FASTON, .250 SERIES	
1 PLC ± -		PRODUCT SPEC		-	
2 PLC ± -		APPLICATION SPEC		-	
3 PLC ± 0.25 [.010]		SIZE		A2	
4 PLC ± - ± -		CAGE CODE		00779	
ANGLES ± -		DRAWING NO		G-42100	
MATERIAL SEE ABOVE		FINISH SEE ABOVE		RESTRICTED TO	
WEIGHT -		SCALE		5:1	
CUSTOMER DRAWING		SHEET		1 of 1	
		REV		AP	