

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:

DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (USE MATH MODEL FOR PRECISION DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. R 0.4 PERMISSIBLE ON ALL "SHARP" CORNERS
3. RECOMMENDED MATING BLADE 2.8×0.81 .
4. TERMINALS TO CRIMP EQUIVALENT AND RETAIN CAVITY SEAL 12015323 OR EQUIVALENT.
5. "PXX" INDICATES "P" PLUS LAST TWO DIGITS OF MAKE SERIES NUMBER (P01, P02, P03, ETC.).
6. DO NOT PROBE, TEST OR OTHERWISE CONTACT THE INTERIOR REGION (THE SPRING OR ANY MOVING PART) OF THIS TERMINAL. SEVERE DAMAGE CAN OCCUR COMPROMISING THE PERFORMANCE OF THE ELECTRICAL INTERFACE.
7. FOR TERMINALS PACKAGED & STORED IN THE APPROVED MANNER, TARNISH ON SOLDER PLATED SURFACES WILL NOT AFFECT THE PERFORMANCE OF THE PART