

Connectors for Automobiles


Connect with the Best

How to choose connectors Notes on usage User Guide Catalogue PDF

results

Housing 2.3/4.8mm
6189-0555

Product information



(Unit : mm)

3D drawings

Contact us for products

6189-0555

HX sealed series

Housing Inline - Hybrid Bracket fixation

2.3/4.8mm(090/187)


Sealed/Unsealed	sealed
Male/Female	F
Way	10 8(2.3mm) + 2(4.8mm)
Mating parts	6181-0381(HX sealed series)

Materials	PBT
Color	Dark Gray


Contact resistance	Initial 3mΩ Max. after durability tests 6mΩ Max.
Leak current	100μA Max.
Insulation resistance	100MΩ Min.
Seal	Initial 98kPa Min. after durability tests 49kPa Min.

HX sealed series related products


Terminal (6)




2.3mm 8240-4862




2.3mm 8240-4992




2.3mm 8240-4952



4.8mm 8100-0661




4.8mm 8100-0660




4.8mm 8100-0468

Hide some results


Wire seals (8)




2.3mm 7165-0385



2.3mm 7165-0194




2.3mm 7165-0198




4.8mm 7165-0172

Show all results

Dummy plugs (2)




[2.3mm 7165-0193](#)



[4.8mm 7165-0145](#)

Connector accessories (1)



[TPA 6918-1267](#)