

This document was generated on 06/22/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | <u>0003061062</u> | | |
|--|-------------------|---|--|
| Status: | Active | | |
| Overview: | Standard .062"+ a | nd Standard .062" Pin and Socket Connector Systems | |
| Description: | | Standard .062" Pin and Socket Receptacle Housing, 6 Circuits, | |
| Documents: | | | |
| Drawing (PDF) | | Product Specification PS-02-06-001 (PDF) | |
| <u>3D Model (PDF)</u> | | Packaging Specification PK-1625-003-001 (PDF) | |
| 3D Model | | RoHS Certificate of Compliance (PDF) | |
| | | | Series image - Reference only |
| Agency Certification | า | | |
| CSA | | LR19980 | EU ELV |
| UL | | E29179 | Not Relevant |
| General | | | EU RoHS China RoHS |
| Product Family | | Crimp Housings | Compliant |
| Series | | 1625 | REACH SVHC |
| Application | | Power, Wire-to-Wire | Not Contained Per - |
| Comments | | Polarized to Mating Part | D(2020)9139-DC (19 |
| Overview | | Standard .062"+ and Standard .062" Pin and Socket | Jan 2021) |
| | | Connector Systems | Halogen-Free |
| Product Name | | Standard .062" | Status |
| UPC | | 800753618718 | Low-Halogen |
| Dhysical | | | For more information, please visit Contact US |
| Physical Breakaway | | No | China DOUIC Cross Image |
| Circuits (maximum) | | 6 | China ROHS Green Image ELV Not Relevant |
| Circuits Detail | | 2x3 | RoHS Phthalates Not Contained |
| Color - Resin | | Natural | |
| Flammability | | 94V-2 | |
| Gender | | Receptacle | |
| Glow-Wire Capable | | No | Search Parts in this Series |
| Keying to Mating Part | | None | <u>1625</u> Series |
| Lock to Mating Part | | Yes | |
| Material - Resin | | Nylon | Mates With |
| Net Weight | | 1.519/g | <u>03062061</u> , <u>03062062</u> , <u>03067061</u> |
| Number of Rows | | 3 | |
| Packaging Type Panel Mount | | Bag No | Use With |
| Pitch - Mating Interface | | 3.68mm | Female Crimp Terminals <u>1561</u> , <u>4559</u> , <u>4529</u> |
| Pitch - Termination Interface | | 3.68mm | , <u>2190</u> , <u>2189</u> , <u>1787</u> , <u>1855</u> . Male Crimp Terminals <u>1560</u> , <u>1786</u> , <u>1854. 1778</u> Male |
| Polarized to Mating P | | Yes | PC Tail Terminals. <u>1779</u> Female PC Tail |
| Stackable | | No | Terminals |
| Temperature Range - | - Operating | -40° to +105°C | Terminaio |
| Electrical | | | |
| Current - Maximum p | er Contact | 5.0A | |
| | | 0.071 | |
| Solder Process Data | | | |
| Lead-freeProcess Ca | pability | N/A | |
| Material Info | | | |
| Engineering Number | | 1625-6R1 | |
| | | | |
| Reference - Drawing | | DK 1625 002 001 | |
| Packaging Specificati Product Specification | | PK-1625-003-001 PS-02-06-001 | |
| | | F 0-02-00-00 I | |

This document was generated on 06/22/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION