

UNINSULATED END SLEEVES TYPE KE for flexible copper cables




Description:

The KE ranges of end sleeves are manufactured from tin plated electrolytic copper. Designed and developed to reinforce the fine wire strands, when terminating a cable into a connector block.

Technical details:

- The connectors are manufactured from Copper Cu DHP UNI 5649/1988 (corresponding to: SF-Cu DIN 1787/1973 Cu/bI NFA 51-050)
- Tin plated with a minimum thickness of 3µm.



Conductor Size sqmm	Ref.	Dimensions mm			Quantity Box/Bag
		ø	L	C	
0,5	*KE 506 ST	1,0	6,0	1,9	50.000/500
	KE 508 ST	1,0	8,0	1,9	50.000/500
0,75	*KE 7506 ST	1,2	6,0	2,2	50.000/500
	KE 7508 ST	1,2	8,0	2,2	50.000/500
1	*KE 106 ST	1,4	6,0	2,4	25.000/500
	*KE 110 ST	1,4	10,0	2,4	25.000/500
1,5	KE 1508 ST	1,7	8,0	2,8	25.000/500
	*KE 1510 ST	1,7	10,0	2,8	25.000/500
2,5	KE 2508 ST	2,2	8,0	3,4	25.000/500
	*KE 2510 ST	2,2	10,0	3,4	15.000/500
4	KE 410 ST	2,8	10,0	4,0	12.500/500
	*KE 412 ST	2,8	12,0	4,0	12.500/500
	*KE 610 ST	3,5	10,0	4,7	10.000/500
6	*KE 612 ST	3,5	12,0	4,7	7.500/500
	*KE 616 ST	3,5	15,0	4,7	5.000/500
10	*KE 1016 ST	4,5	15,0	5,8	4.000/250
16	*KE 1616 ST	5,8	15,0	7,5	3.000/250
25	KE 25015 ST	7,3	15,0	9,5	1.500/100
	*KE 25018 ST	7,3	18,0	9,5	1.500/100
35	KE 35012 ST	8,3	12,0	10,5	1.500/100
	KE 35015 ST	8,3	16,0	10,5	1.500/100
	*KE 35018 ST	8,3	18,0	10,5	1.000/100

*To DIN standard 46 228/1



**THORNE &
DERRICK
INTERNATIONAL**

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com