

# **Steering Wheel Angle Sensor LWS**



► Steering Wheel Angle: ± 780°

► Angular Speed: 0 to 1,016°/s

▶ 500 kbaud CAN-output

This sensor is designed to measure rotational movement and angular speed, e.g. steering wheel angle and steering wheel speed.

In order to achieve this, the sensor is using the giant magneto resistive (GMR) effect. The detection of the absolute angle is realized by means of toothed measuring gears with different ratio including small magnets. Corresponding GMR elements that change their electrical resistance according to the magnetic field direction detects the angle position of the measuring gears.

The measured voltages are A/D converted and a microcontroller performs the angle calculations. The steering angle and the steering angle speed are provided on a CAN-interface.

Application	
Steering wheel angle	± 780°
Angular speed	0 to 1,016°/s
Operating temperature range	-40 to 85°C

# **Technical Specifications**

## **Mechanical Data**

Approx. 34 g
83 x 60 x 21.35 mm
IP5K0

## **Electrical Data**

Power supply	7 to 16 V
Max input current	< 150 mA
CAN speed	500 kbaud

## **CAN Message**

CAN ID 01 0x2B0 LWS_Standard				
Byte	Value / Bit			
	7/6/5/4/3	2	1	0
0	LWS_ANGLE			
1	LWS_ANGLE			
2	LWS_SPEED			
3	Reserved	TRIM	CAL	OK
4	Reserved			
CAN ID 02 0x7C0 LWS_Config				
Byte	Value / Bit			
	7/6/5/4/3	2	1	0
0	Reserved	CCW		
1	Reserved			

#### **Truth Table**

TRIM	OK	CAL	ANGLE	SPEED	Sensor state
1	1	1	Value	Value	Sensor is calibrated and sensor information is valid.
1	1	0	7FFFh	Value	Sensor is not calibrated, speed information is valid.
1	0	0	7FFFh	FFh	Sensor is in failure mode, sensor information is not valid.
0	0	0	7FFFh	FFH	Sensor is in failure mode, sensor information is not valid.

Other combinations for TRIM, OK and CAL are not valid.

## Signal Overview

OK	Failure status
1	Sensor information valid

OK	Failure status
0	Sensor information invalid, an internal sensor fault occurred
CAL	Calibration status
1	Sensor calibrated
0	Sensor not calibrated
TRIM	Trimming Status
1	Sensor trimmed
0	Sensor not trimmed, this is handled as a sensor failure (OK = 0)
CCW	Command code word
3h	Sets the signal LWS_Angle to 0°
5h	Resets the calibration status of the angle

#### **Characteristics**

Steering Wheel Angle	
Measuring range	± 780°
Absolute physical resolution	0.1°
Nonlinearity	± 2.5°
Hysteresis	0 to 5°
Angular Speed	
Measuring range	0 to 1,016°/s
Over range limit	± 2,500°/s
Absolute physical resolution	4°/s

#### **Connectors and Wires**

Connector	Bosch 7 pole
Mating connector	F02U.B00.656-01
Pin 1	Gnd
Pin 2	12 V
Pin 3	CAN High
Pin 4	CAN Low
Pin 5	Not connected

Pin 6	Not connected
Pin 7	Not connected

#### **CAN Parameters**

Byte order	LSB (Intel)
CAN speed	500 kbaud
CAN update rate	100 Hz / 10 ms

## **Installation Notes**

The LWS can be connected directly to most control units and data logger systems via CAN bus.

Please avoid abrupt temperature changes.

Please ensure that the environmental conditions do not exceed the sensor specifications.

Please find further application hints in the offer drawing.

A zero adjustment is needed before using the sensor for the first time. To do so, reset the calibration with CCW = 5h. After resetting the calibration, a new calibration needs to be started with CCW = 3h. The sensor is now newly calibrated and can be used immediately.

Zero the sensor after every assembly.

## **Safety Note**

The sensor is not intended to be used for safety related applications without appropriate measures for signal validation in the application system.


## **Legal Restrictions**


Due to embargo restrictions, sale of this product in Russia, Belarus, Iran, Syria, and North Korea is prohibited.

## **Ordering Information**

Steering Wheel Angle Sensor LWS Order number F02U.V02.894-01

## **Dimensions**





Housing Size

## Represented by:

Europe:
Bosch Engineering GmbH
Motorsport
Robert-Bosch-Allee 1
74232 Abstatt
Germany
Tel.: +49 7062 911 9101
Fax: +49 7062 911 79104
motorsport@bosch.com
www.bosch-motorsport.de

North America:
Bosch Engineering North America
Motorsport
38000 Hills Tech Drive
Farmington Hills, MI 48331-3417
United States of America
Tel.: +1 248 876 2977
Fax: +1 248 876 7373
mptorsport/phosch com motorsport@bosch.com www.bosch-motorsport.com

Asia-Pacific:
Bosch Engineering Japan K.K.
Motorsport
18F Queen's Tower C, 2-3-5 Minato
Mirai Nishi-ku, Yokohama-shi
Kanagawa 220-6218
Japan
Tel: +81 45 650 5610
Fax: +81 45 650 5611
www.bosch-motorsport.jp

Australia, New Zealand and South Africa: Robert Bosch Pty. Ltd Motorsport 1555 Centre Road Clayton, Victoria, 3168 Australia Tel.: +61 (3) 9541 3901 motor.sport@au.bosch.com

@ Bosch Engineering GmbH 2022 | Data subject to change without notice | , V, 02. Nov 2022